

# AVNET EMBEDDED SPECIFICATION.

**Datasheet**  
Seiko Instruments  
LTP1245

# LTP Series

LTP1245 PRINTER

The LTP1245 is a thermal line printer that offers high-speed, high-resolution printing in a compact, lightweight mechanism ideal for today's 5V portable applications. Providing low-power consumption to support battery-powered operation, the LTP1245 is a maintenance-free mechanism and, with optional interface, allows for automatic paper loading. Ideal for measuring instruments, analyzers, POS, portable communications devices and more, the LTP1245 maximizes printer functionality in applications where minimizing power consumption, size and weight is a priority.

- High resolution printing (8 dots/mm)
- High speed, low voltage printing (25mm @ 5V, 62.5mm @ 8.0V)
- Low 4.2V to 8.5V power supply operation
- Prints on label stock
- Available with or without paper feed knob
- Available with straight or curved paper path (up to 95 µm)
- Thick paper printing possible on straight path
- Automatic paper loading (available with IF1001-01B interface board)
- Wide opening head for easy access
- Wide temperature range



LTP1245

Model		LTP1245
Printing	Method	Thermal line dot system
	No. of dots/line	384
	No. of characters/line	24
	Width (mm)	48
	Resolution	8 dots/mm
	Paper feed pitch (mm)	0.125
	Speed (mm/s)	25 @ 5V, 62.5 @ 8.0V
Detection	Speed (cl/s)	7.5 @ 5V, 12.5 @ 8.0V
	Head temperature	By thermistor
	Paper out detection	By photo interrupter
Dimensions (WxDxH) mm	Head up detection	By photo interrupter
	Weight (g)	72 X 39.5 X 16
Power supply	Operating voltage	4.2 V to 8.5 V
	Current consumption	2.1 Max. @ 5 VDC, 3.3 Max. @ 8.0 VDC 64 dots
Service life	Pulse activation	min. 100 million pulses (12.5% print ratio)
	Abrasion resistance	50km or more
Operating temperature (°C)		-30 to +70 (wide temperature range)
Storage temperature (°C)		-35 to +75
Paper	Width (mm)	58 +0/-1
	Path	Straight or curve
	Thickness (µm)	65 ± 5
Auto cutter	ACU6205	Optional

### ACU6205A/B AUTO CUTTER

The ACU6205 is a compact and lightweight circular cut type automatic cutter developed for the LTP1245 thermal line printer mechanism.

- Full cut and partial cut are available
- Easily mounts on printer mechanism, opens for easy maintenance



### IF1001-01B INTERFACE BOARD FOR LTP1245 SERIES

The IF1001-01B is an interface board used specifically for the LTP1245 Series. It is equipped with 8-bit parallel and serial TTL data input terminals. The IF1001-01B brings its printing functions into full play using a wide variety of characters and function commands.

### PT100P01/PT101P01 AND PT120P01 CPU FOR LTP1245 SERIES

- Prints with less current using dynamic division control in accordance with the number of dots to be activated
- Supports both parallel and serial input
- Ensures high-quality print by measuring the temperature and voltage, and adjusting the print density
- Provides a wide variety of user-defined character functions including double-width/double-height, inverse print, underlining, and character spacing control; character string
- Supports bit image graphics and characters
- Provides a ruler line function which enables ruler lines and characters to be easily superimposed
- Stamp function
- Auto paper loading function

Model	IF1001-01B
Applicable mechanism	All LTP1245 Series
CPU	PT100P01/PT500GA1
Input control method	8-bit parallel (modified Centronics) Serial (TTL level)
Character type	222-IBM compatible 126-Japanese kana
Dimensions (WxDxH) mm	70.0 x 100.0 x 12.0
Weight (g)	40
Operating voltage (Vcc)	-5 VDC ± 0.5
Current consumption (Icc)	Max. 20 mA @ 5 VDC (standby) Max. 200 mA @ 5 VDC (printing)
Operating temperature (°C)	-5 to 50
Storage temperature (°C)	-20 to 60
Model	PT100P01 / PT101P01
Applicable mechanism	All LTP1245 Series
Package form	80-pin flat package
Dimensions (WxDxH) mm	22.8 x 16.8 x 3.05
Configuration	C-MOS LSI
Input method	8-bit parallel (Centronics), Asynchronous serial
Operating voltage (Vcc)	5 VDC ± 0.5
Operating frequency (MHz)	16 ± 0.5%
Remarks	Use these CPUs and a gate array (PT500GA1) as a pair PT101P01 for use with auto cutter PT120P01 for use w/o gate array
Model	ACU6205A/B
Cut Method	Circular cutter type
Cut width (mm)	58 mm
Cut condition	full cut / partial cut
Drive voltage (VDC)	Motor 4.2V to 6.0V Detector 5V ± 10%
Starting current (A)	1.2A max.
Operating time (ms/cycle)	0.6 sec. (max.) at 6.0 V
Cut frequency (cuts/minute)	30 max.
Life (cuts)	300,000 (M.C.B.F.)
Dimensions (WxDxH) mm	81.9 x 54 x 12
Weight (g)	50
Operating temperature (°C)	0 to 50
Storage temperature (°C)	-20 to 60
Paper thickness (µm)	75

## AVNET EMBEDDED OFFICES.

### DENMARK

Avnet Embedded  
Avnet Nortec A/S  
Ellekær 9  
2730 Herlev  
Phone: +45 3678 6250  
Fax: +45 3678 6255  
denmark@avnet-embedded.eu

### FINLAND

Avnet Embedded  
Avnet Nortec Oy  
Tiilenpolttajankuja 3 A B  
1720 Vantaa  
Phone: +358 207 499260  
Fax: +358 942 597446  
finland@avnet-embedded.eu

### FRANCE

Avnet Embedded  
Avnet EMG France SA  
Immeuble 154, Parc Chene 2  
5, allée du General Benoist  
69000 Bron  
Phone: +33 4 72 81 02 30  
Fax: +33 4 72 81 02 34  
axess-bron@avnet-embedded.eu

Avnet Embedded  
Avnet EMG France SA  
4, rue de la Couture  
Bâtiment Milan, BP 20209  
94518 Rungis Cedex  
Phone: +33 1 49 78 88 88  
Fax: +33 1 49 78 88 89  
axess-rungis@avnet-embedded.eu

Avnet Embedded  
Avnet EMG France SA  
ZA la Hallerais le Semiramis  
2, allée du Communal  
35770 Vern sur Seiche  
Phone: +33 2 99 77 37 02  
Fax: +33 2 99 77 33 38  
axess-rennes@avnet-embedded.eu

### GERMANY (AUSTRIA, CZECH REPUBLIC, HUNGARY, POLAND, SWITZERLAND)

Avnet Embedded  
Avnet EMG GmbH  
Gruber Straße 60c  
85586 Poing  
Phone: +49 8121 775 500  
Fax: +49 8121 775 550  
poing@avnet-embedded.eu

Avnet Embedded  
Avnet EMG GmbH  
Lötscher Weg 66  
41334 Nettetal  
Phone: +49 8121 775 500  
Fax: +49 8121 775 550  
nettetal@avnet-embedded.eu

### ITALY (PORTUGAL, SPAIN)

Avnet Embedded  
Avnet EMG Italy SRL  
Via Manzoni, 44  
20095 Cusano Milanino  
Phone: +39 02 66092 1  
Fax: +39 02 66092 498  
milano@avnet-embedded.eu

### NETHERLANDS (BELGIUM, LUXEMBOURG)

Avnet Embedded  
Avnet B.V.  
Takkebijsters 2  
4802 BL Breda  
Phone: +31 76 5722400  
Fax: +31 76 5722404  
benelux@avnet-embedded.eu

### SWEDEN (NORWAY)

Avnet Embedded  
Avnet Nortec AB  
Esplanaden 3 D  
172 67 Sundbyberg  
Phone: +46 8 564 725 50  
Fax: +46 8 760 01 10  
sweden@avnet-embedded.eu

### UNITED KINGDOM (IRELAND)

Avnet Embedded  
Avnet EMG Ltd.  
Pilgrims Court, 15/17 West Street  
Reigate, Surrey, RH2 9BL  
Phone: +44 1737 227800  
Fax: +44 1737 243872  
uk@avnet-embedded.eu

All trademarks and logos are the property of their respective owners. This document provides a brief overview only and is not intended to be complete or binding offer. Product information, including information related to a product's specifications, uses or conformance with legal or other requirements, is obtained by Avnet from its suppliers or other sources deemed reliable and is provided by Avnet on an „As Is“ basis. Avnet makes no representation as to the accuracy or completeness of the product information and Avnet disclaims all representations, warranties and liabilities under any theory with respect to the product information, including any implied warranties of merchantability, fitness for a particular purpose, title and/or non-refrangement. All product information is subject to change without notice.

### LOCAL AVNET EMBEDDED BUSINESSES:

**axess**  
technology

An Avnet Embedded Business

**tdc**

An Avnet Embedded Business

**trident**

An Avnet Embedded Business