

# AVNET EMBEDDED SPECIFICATION.

**Datasheet**  
Seiko Instruments  
LTPV345\_445

# LTP Series

LTPV345/LTPV445 PRINTER

LTPV345 and LTPV445 of Seiko Instruments are new 3" and 4" thermal line dot printer mechanisms which belong to the "Easy-Paper-Operation" product-line. They are unique in featuring straight paper paths, i.e. they present the first easy-loading mechanisms suitable for label printing. Paper up to a thickness of 125µm can be printed on. There is also an option of mounting the paper end sensor either on the frame or the platen differing from specific requirements. Finally, both versions can be battery driven. Thus, LTPV series printers are perfectly applicable for measuring instruments and analysers, POS-EFT and ECR as well as for a variety of hand-held applications.

- Straight paper path: label printing possible up to paper thickness of 125µm
- Position of paper end sensor optional: frame or platen
- Improved operability of paper installation and head cleaning by release lever operation
- High resolution printing (8 dots/mm)
- High speed, low voltage printing (45mm/s @ 5V, 85mm/s @ 7.2V)
- Battery operation of 4 to 6 cells Ni-MH / Ni-Cd batteries or 2 cells of lithium-ion batteries for hand-held applications
- Low 4.2V to 8.5V power supply operation
- Design to fit easily into the outer case (reduced number of outer case parts)



Model	LTPV345A-576	LTPV445A-832	
Printing	Method	Thermal line dot printing	
	No. of dots/line	576	832
	Common activatable dots/line	192	192
	Resolution (mm)	8 dots	
	Width (mm)	72	104
	Speed (mm/s)	45 @ 5V, 85 @ 7.2V, 85 @ 8.5V	
	Paper feed pitch (mm)	0.0625	
Detection	Head temperature	By thermistor	
	Lever position detection	By mechanical switch	
	Out-of-paper detection	By photo interrupter	
Dimensions (WXDXH) mm <sup>1</sup>	93 x 34.5 x 39.5 mm	125 x 34.5 x 39.5 mm	
Weight (g)	appr. 95	appr. 115	
Power supply	Operating voltage	Vp line: 4.2V to 8.5 V; Vdd line: 5V +/- 5%	
	Current consumption <sup>2</sup>	1.96A max. @ 5V, 2.82A max. @ 7.2V, 3.33A max. @ 8.5V	
Service life	Pulse activation	100 million pulses or more	
	Abrasion resistance	50km or more	
Operating temperature (°C)	0 to +50		
Storage temperature (°C)	-20 to +60		
Paper	Width (mm)	80	112
	Paper feed force	0.49N (50gf) or more	
	Paper hold force	0.78N (80gf) or more	
	Thickness	125µm	

<sup>1</sup> Excluding the lever projections

<sup>2</sup> When the number of activated dots is specified as 64

## INTERFACE BOARD & CPU

### IFV001-01B INTERFACE BOARD FOR LTPV345 AND LTPV445

The interface IFV001-01B is an interface used with LTPV series printers. It processes and converts data input sent from a host device. The IFV001-01B is compatible with both parallel and serial data input. It prints extended character sets as well as bit images. Furthermore, the interface provides an output of internal test patterns and informs about the status of the printer.

### PTV00P01 CPU FOR LTPV345 AND LTPV445

- For individual design-in into various applications
- Drives LTPV345 and LTPV445 printer mechanisms
- Supports both parallel and serial input
- Provides high quality printing by automatically adjusting print density according to temperature and voltage
- Reduces consumption current using the power saving function
- Registers and prints any font using the downloaded character function and the user-defined character function
- Downloaded characters, user-defined characters, option fonts, character strings, stamps etc. can be stored in external ROM
- Prints barcodes using the barcode print function

Model	IFV001-01B	
Application	LTPV series printer mechanism	
Character type	Extended graphics character set Downloaded characters User-defined characters Optional font	
Character configuration	16-dot Standard size character 16x8 Kanji size character 16x16	24-dot 24x12 <sup>1</sup> 24x24 <sup>1</sup>
Input control method	Parallel (modified Centronics) Serial (C-MOS level)	
No. of characters/line <sup>2</sup>	36	52
Line spacing	16 dots <sup>1</sup>	
Character spacing	4 dots <sup>1</sup>	
Maximum print speed <sup>3</sup>	45.1 @ 5V, 85 @ 7.2V, 85 @ 8.5V4	
Operating voltage range	Vcc 5V +/- 10% Vp 4.2V to 8.5V	
Current consumption (Icc) <sup>5</sup>	Printing 100mA max. Stand by 25mA max. Stop mode 12mA max.	
Operating temperature (°C)	0 to +50	
Storage temperature (°C)	-20 to +60	
Dimensions (WxDxH) mm	70 x 60 x 10.6	
Weight (g)	appr. 28	

<sup>1</sup> The default value is changeable through commands

<sup>2</sup> 24-dot standard size character, character spacing 4 dots

<sup>3</sup> Dynamic division 64 dots, 24-dot font standard size character, 16-dot line spacing, 4-dot character spacing, number of simultaneously activated dots is 64 or less

<sup>4</sup> Respectively for LTPV345 and LTPV445

<sup>5</sup> Vcc = 5V, 25°C, no error, when no input/output terminal is connected.

Model	PTV00P01	
Applicable printer	LTPV345	LTPV445
Package type	80 pin flat package	
Dimension (WxDxH) mm	22.8 x 16.8 x 3.05	
Configuration	C-MOS LSI	
Character type	Extended graphics character set Katakana character set <sup>1</sup> JIS 1st and 2nd level Kanji, Chinese, Korean <sup>1</sup> Downloaded characters <sup>2</sup> User-defined characters Option font <sup>2</sup>	
Input control method	Parallel (simplified Centronics) Serial (2400-38400 bpc, C-MOS level)	
Operating voltage	Vcc 5V +/- 10% Vp 4.2V to 8.5V	
Operating frequency	25 MHz +/- 0.5%	
Current consumption <sup>3</sup>	Printing 100mA Standby 25mA Stop mode 12mA	
Operating temperature (°C)	0 to +50	
Storage temperature (°C)	-20 to +60	
Remark	Use this CPU and a gate array (PT301GA1) as a pair	

<sup>1</sup> To print Kanji / Katakana characters, the Japanese CG (PTJCG2) is necessary. To print Chinese / Korean characters, the respective CGs for Chinese and Korean are necessary.

<sup>2</sup> External RAM or ROM must be needed.

<sup>3</sup> Vcc = 5V, 25°C, no error, when input/output terminal is not connected.

## AVNET EMBEDDED OFFICES.

### DENMARK

Avnet Embedded  
Avnet Nortec A/S  
Ellekær 9  
2730 Herlev  
Phone: +45 3678 6250  
Fax: +45 3678 6255  
denmark@avnet-embedded.eu

### FINLAND

Avnet Embedded  
Avnet Nortec Oy  
Tiilenpolttajankuja 3 A B  
1720 Vantaa  
Phone: +358 207 499260  
Fax: +358 942 597446  
finland@avnet-embedded.eu

### FRANCE

Avnet Embedded  
Avnet EMG France SA  
Immeuble 154, Parc Chene 2  
5, allée du General Benoist  
69000 Bron  
Phone: +33 4 72 81 02 30  
Fax: +33 4 72 81 02 34  
axess-bron@avnet-embedded.eu

Avnet Embedded  
Avnet EMG France SA  
4, rue de la Couture  
Bâtiment Milan, BP 20209  
94518 Rungis Cedex  
Phone: +33 1 49 78 88 88  
Fax: +33 1 49 78 88 89  
axess-rungis@avnet-embedded.eu

Avnet Embedded  
Avnet EMG France SA  
ZA la Hallerais le Semiramis  
2, allée du Communal  
35770 Vern sur Seiche  
Phone: +33 2 99 77 37 02  
Fax: +33 2 99 77 33 38  
axess-rennes@avnet-embedded.eu

### GERMANY (AUSTRIA, CZECH REPUBLIC, HUNGARY, POLAND, SWITZERLAND)

Avnet Embedded  
Avnet EMG GmbH  
Gruber Straße 60c  
85586 Poing  
Phone: +49 8121 775 500  
Fax: +49 8121 775 550  
poing@avnet-embedded.eu

Avnet Embedded  
Avnet EMG GmbH  
Lötscher Weg 66  
41334 Nettetal  
Phone: +49 8121 775 500  
Fax: +49 8121 775 550  
nettetal@avnet-embedded.eu

### ITALY (PORTUGAL, SPAIN)

Avnet Embedded  
Avnet EMG Italy SRL  
Via Manzoni, 44  
20095 Cusano Milanino  
Phone: +39 02 66092 1  
Fax: +39 02 66092 498  
milano@avnet-embedded.eu

### NETHERLANDS (BELGIUM, LUXEMBOURG)

Avnet Embedded  
Avnet B.V.  
Takkebijsters 2  
4802 BL Breda  
Phone: +31 76 5722400  
Fax: +31 76 5722404  
benelux@avnet-embedded.eu

### SWEDEN (NORWAY)

Avnet Embedded  
Avnet Nortec AB  
Esplanaden 3 D  
172 67 Sundbyberg  
Phone: +46 8 564 725 50  
Fax: +46 8 760 01 10  
sweden@avnet-embedded.eu

### UNITED KINGDOM (IRELAND)

Avnet Embedded  
Avnet EMG Ltd.  
Pilgrims Court, 15/17 West Street  
Reigate, Surrey, RH2 9BL  
Phone: +44 1737 227800  
Fax: +44 1737 243872  
uk@avnet-embedded.eu

All trademarks and logos are the property of their respective owners. This document provides a brief overview only and is not intended to be complete or binding offer. Product information, including information related to a product's specifications, uses or conformance with legal or other requirements, is obtained by Avnet from its suppliers or other sources deemed reliable and is provided by Avnet on an „As Is“ basis. Avnet makes no representation as to the accuracy or completeness of the product information and Avnet disclaims all representations, warranties and liabilities under any theory with respect to the product information, including any implied warranties of merchantability, fitness for a particular purpose, title and/or non-refrangement. All product information is subject to change without notice.

### LOCAL AVNET EMBEDDED BUSINESSES:

**axess**  
technology

An Avnet Embedded Business

**tdc**

An Avnet Embedded Business

**trident**

An Avnet Embedded Business